

OptiFit FTTx Fiber Drop Cables

Available in Single or
Multi Fiber Modes

For Use with FTTx Service Drops

Custom Cable Lengths

Environmentally Hardened,
Sealed, and Strain-Relieved
Connectors



Tii's OptiFit Drop Cable Assemblies feature environmentally hardened, sealed and strain-relieved connectors that are factory-terminated on one or both ends of optical drop cables. These assemblies are custom made to required length to save service providers and installers considerable time and money when deploying FTTx networks and eliminate the need for fusion splicing for drop cable installation and subscriber connection.

KEY PRODUCT BENEFITS

- Aerial, direct burial, duct installation
- Environmentally sealed Corning OptiFit APC connector
- Integrated pulling eye connector cap, can be pulled through 1.25" conduit
- Available with OptiFit both ends or pigtail assemblies
- All dielectric or tonable flat drop cable

ORDERING INFORMATION

R1C5	—X	8-OT	—XX	XXX	X
	Jacket		End B	Length	UOM
	N = All Dielectric		OT = OptiFit	3 Digit, e.g. 001	F = Feet
	V = Tonable		NA = Pigtail		M = Meters



Tii Technologies Inc.

Corporate Headquarters:
141 Rodeo Drive
Edgewood, NY 11717
Phone: 631.789.5000
Toll Free: 888.844.4720
sales@tiitech.com