

QT Series

Quick Termination Field Installable Connectors

CPE/Premise Wiring

Headend/CO

FTTx

MDU

Utility/Municipality

Wireless



Pre-polished, pre-assembled field installable connector compatible with the standard SC and LC interface. Internal mechanical splice grip gently but effectively holds the fiber in place and can be installed in under two minutes. The QT series connectors makes field installations quick and easy, eliminating the need for epoxy curing and hand polishing at the work site. The connector packs include an assembling jig and fiber holder, making for an accurate alignment and fiber cleave when terminating the connector. Installing the QT series connectors require typical technician hand tools and a precision fiber cleaver or an optional complete installation tool kit is available.

KEY PRODUCT BENEFITS

- ▶ Mechanical splice (index matching gel)
- ▶ 250 or 900um fiber installations
- ▶ Fiber can be removed and reinserted

INDUSTRY STANDARDS

- ▶ Meets G.657
- ▶ A1, A2, B1 Compliant
- ▶ UL94-V0 and RoHS compliant



Tii Technologies Inc.

Corporate Headquarters:

141 Rodeo Drive
Edgewood, NY 11717
Phone: 631.789.5000
Fax: 631.789.5063
Toll Free: 888.844.4720
sales@tiitech.com

Quick Termination Connectors

SPECIFICATIONS

	Singlemode	Multimode
Insertion Loss	0.2 dB (UPC) / 0.3 dB (APC)	0.4 dB
Return Loss	55 dB (UPC) / 60 dB (APC)	35 dB
Durability	0.1 dB change 500 matings	
Temperature Range	-40° to 75° C	
Tensile Strength	TIA/EIA 568.B3	
Intermateability	IEC 61754-4 & TIA/EIA 604 FOCUS	

ORDERING INFORMATION

Model No.	Description
QT-SCR	SC UPC Singlemode for 250um or 900um
QT-SAR	SC APC Singlemode for 250um or 900um
QT-SCC	SC PC Multimode 50um for 250um or 900um
QT-SCK	SC PC Multimode 62.5um for 250um or 900um
QT-LCR	LC UPC Singlemode for 250um or 900um
QT-LCC	LC PC Multimode 50um for 250um or 900um
QT-LCK	LC PC Multimode 62.5um for 250um or 900um
QT-KIT	QT connector installation Tool Kit

Connectors are ordered in multiples of 100 pieces.

Package includes:

- ▶ 100 connectors
- ▶ 100 boots 900um
- ▶ 100 furcation tube 250/900um
- ▶ 2 fiber holders
- ▶ 2 assembly jigs