

## TRM Series

### Terminators

Central Office

CATV

Laboratories

Field Testing



Optical terminators are used to terminate unused connector ports in fiber optic systems so that unwanted reflections are not introduced back into the system. Available in FC, LC, SC and ST.

#### KEY PRODUCT BENEFITS

- ▶ Doped Fiber Technology
- ▶ Low Backreflection
- ▶ High Durability over High Power

#### INDUSTRY STANDARDS

- ▶ EIA/TIA-604 FOCIS

#### SPECIFICATIONS

Wavelength	1250 - 1650nm
Maximum Power	500mw
Return Loss	55dB UPC, 65dB APC
Temperature Range	-40° to +85°C

#### ORDERING INFORMATION

Model #	Description
TRM-2-3-1	Terminator FC APC
TRM-2-2-1	Terminator FC UPC
TRM-4-3-1	Terminator LC APC
TRM-4-2-1	Terminator LC UPC
TRM-1-3-1	Terminator SC APC
TRM-1-2-1	Terminator SC UPC
TRM-3-2-1	Terminator ST UPC



Tii Technologies Inc.

Corporate Headquarters:

141 Rodeo Drive

Edgewood, NY 11717

Phone: 631.789.5000

Fax: 631.789.5063

Toll Free: 888.844.4720

sales@tiitech.com