

Tii RM5UWS

Rackmount Fiber Distribution Enclosure

Accommodates Up to 288 Fiber Ports

Available in Various Fiber Adapter Connections

Multiple Pigtail and Splice Tray Options Available

LG7 Series Adapter Plates in White

Used in Telecom Closets, Central Offices, Data Centers and Remote Distribution Terminals



Tii RM5UWS

The RM5UWS Fiber Termination Panel provides connectivity up to 144 Ports (288 ports LC only). The 5RU shelf accepts 12 LGX 170 long adapter panels and offers integrated mass ribbon fiber splicing module. 900um pigtails and splicing is available with the optional 3RU SPS-5 splice bay installed. TSL shelves have been designed to meet Telcordia GR-63 and GR-449 Fiber Distribution Frame System requirements.

KEY PRODUCT BENEFITS

- ▶ Available with factory loaded adapter plates, splice trays and pigtails
- ▶ 19 or 23" rack mountable
- ▶ Integrated ribbon splice module
- ▶ LGX compatible adapter plates
- ▶ Patch or patch and splice

INDUSTRY STANDARDS

- ▶ Xxx



tii network technologies

141 Rodeo Drive
 Edgewood, NY 11717
 T. 631. 789.5000
 Toll Free 888.844.4720
 F. 631. 789.5063
 sales@tiinettech.com

Tii RM5UWS

Dimensions are in Inches

SPECIFICATIONS

ORDERING INFORMATION Model Number Matrix

Tii RM5UWS	-XXX	-X	-XX	-X
	Fiber Ports	Fiber Type	Adapter	Pigtails & Splice Trays
	144	R = Singlemode	FC - FC	N = None
	288 (LC only)	K = MM62.5 OM1	FA - FC APC	9 = 900um
		C = MM50 OM2	LC - LC	R = 12 Fiber Ribbon
		S = MM50 OM3	SC - SC	
			SA - SC APC	
			ST - ST	