88X-(XXX)C Series

Terminal Block with RJ21/Wire Wrap Termination

CPE/Premise Wiring

Headend/CO

Utility/Municipality



Corporate Headquarters:

141 Rodeo Drive Edgewood, NY 11717 Phone: 631.789.5000 Fax: 631.789.5063 Toll Free: 888.844.4720 sales@tiitech.com



88-(XXX)C Equipment Terminal Blocks are used to terminate the exchange equipment pairs on the horizontal side of a conventional main distribution frame (MDF), and provide the cross-connect field for jumpering to the Outside Plant (OSP) vertical side of the frame. They also feature CAT5 compliance for superior transmission of DSL signals and other high frequency circuits.


KEY PRODUCT BENEFITS


- ► Eight-inch block accommodates most conventional horizontal frame mounting configurations
- Mounting bracket included for easy installation
- ▶ RJ21 connectorized input field to allow easy connection of equipment
- Up to 256-pair wire-wrap output termination provides maximum density
- Complies with Telcordia specifications
- Special housing allows neat and organized administration of the incoming cross-connect pairs
- Flat face allows use in tight quarters such as cabinets and vaults
- Internal twisted pair wiring provides CAT5 rated performance for superior transmission of DSL and other high frequency applications
- Ample designation areas on both front and back of the cover
- Designation label included


INDUSTRY STANDARDS

Complies with Telcordia specifications

88X-(XXX)C Series







Bottom View

Dimensions are in Inches

SPECIFICATIONS

Pair Count	Dimensions (HxWxD)
100-256	4.2" x 8.0" x 6.4" (10.67 cm x 20.32 cm x 16.26 cm)

COMMON CONFIGURATIONS

Model No.	Pair Count	Housing	Input	Output
88-100CM	100	4.75"	25-Pair RJ21 (Male)	Wire Wrap
88-128CM	128	4.75"	32-Pair RJ21 (Male)	Wire Wrap
88-150CM	150	4.75"	25-Pair RJ21 (Male)	Wire Wrap
88-192CM	192	6.34"	32-Pair RJ21 (Male)	Wire Wrap
88-200CM	200	6.34"	25-Pair RJ21 (Male)	Wire Wrap
88-256CM	256	6.34"	32-Pair RJ21 (Male)	Wire Wrap

ORDERING INFORMATION

88	X	— XXX C		X	X
	OPTION	PAIR COUNT		CONNECTOR PIN OUT	INPUT
	Blank = Wire Wrap	96 Pair (8 x 24)	A	Blank = USOC Pair 1, Pins 1 & 26	F = RJ21 Female
		100 Pair (8 x 25)		5 = CAT5 Pair 1, Pins 1 & 2	M = RJ21 Male
		128 Pair (8 x 32)			
		150 Pair (12 x 25)			
		192 Pair (12 x 32)			
		200 Pair (16 x 25)			
		256 Pair (16 x 32)			